

GOT SILK?

When it comes to finish a wood floor, make sure you are not out of stock. Silk, single component waterborne, clear, durable finish.



- ✓ Low environmental impact certified EC1
- ✓ Exceptional resistance to abrasion and
- ✓ to scuff marks
- ✓ Great transparency
- ✓ Non yellowing
- ✓ Good toning effect



SILK, single component waterborne, clear, durable finish.

Single component waterborne, clear, durable finish available in the versions X-MATT, Satin, Semigloss and High gloss. Exceptionally resistant to abrasion and scuff marks, SILK is ideal for use in every situation. From the point of view of appearance, it differs from traditional waterborne products due to its considerable transparency, the cleanliness of the film and, above all, the warm tone that it confers on the wood, avoiding the "whitening" typical of other waterborne finishes. The EC1 classification certifies the very low emission of volatile organic compounds both during application of the product and when the floor is in use.

Technologies

The great performance of SILK are also due to the use of unique technologies developed by Vermeister laboratories.

SELF CROSS-LINKING SYSTEM | The Self Cross-Linking System S-XL, enables compounds to be added to the coatings that activate after the evaporation of the water and give rise to a true chemical cross-linking. In this way performances are achieved similar to those of two component coatings with single component coatings as if component B had already been added to them.



Certified reliability


EC 1 CERTIFIED Particular consideration must be given to the healthiness of the air when choosing chemical products to be used for installing wood floors indoors. Those wishing to achieve the maximum level of protection for the health, environmental cleanliness and quality of the indoor air must refer to the EMICODE EC1® quality mark. The products classified as "very low emission" and bearing the GEV EMICODE EC1® mark offer the best guarantee against indoor air pollution and a very high level of protection for the health and environmental compatibility.



NMP-FREE NMP (N-methyl-2-pyrrolidone) is a solvent used in the production of water based finishes classified with negative effects on the reproductive cycle. Since 2007 Vermeister has decided to market only water based products that are NMP free, in view of the possible risk raised.



INDOOR AIR EMISSIONS In France, as from 1st January 2012, construction products installed indoors must bear a label certifying, in a specific and simple way, their level of emission of volatile organic compounds. The level of emission of the product is shown by a class which ranges from A+ (very low emissions) to C (high emissions). Vermeister products in the Zero concept and Innovation ranges (as well as some products in other ranges) fall within the A+ class. The purpose of this labelling is to provide consumers with clear information about the VOC (volatile organic compounds) emitted by the products after 28 days of testing.



Maintenance

The maintenance of floors finished with SILK must only be carried out using DETERGENTE NEUTRO and/or IDRONET. Do not use alcohol, ammonia or detergents for hard surfaces.

