

**DESCRIPTION**

Mixture of slow evaporation solvents to increase the open time and the finish application time during hotter weather and to make more demanding jobs easier to perform. The unique characteristic of this product is its VOC value which enables it to be used in those products subject to the restrictions prescribed by EC Directive 2004/42 as it does not increase the total content of volatile organic compounds (maximum limit 500 g/l).

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 20°C (indicative values not constituting product specifications):

Standard packaging (Lt)

5

5 Lt

**APPLICATION**

Dilute the finish with a quantity of between 5 and 10% of RITARDANTE LOW VOC and apply as usual. The addition of larger quantities could compromise the coverage of the finish and prolong the interval before sanding, if required.

NOTES

In colder periods, the addition of RITARDANTE LOW VOC makes the drying time longer.

Safety precautions. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.